

# CLASSICO

thickness: 0.9-1.1MM  
average size: 55 sq. ft  
availability: In Stock  
category: Protected  
finish type: Smooth  
raw material: European  
Made in Italy

Classico is the “go to leather”. It’s aniline dyed and has a protective finish to give Classico a smooth, consistent graining and color. Its suppleness is perfect for residential use yet it’s unique and durable finish will pass the strictest commercial code. This is the largest collection for Optima.

**Colorways available:** Avocado, Baby Camel, Bamboo, Bayou, Black, Charcoal, Chocolate, Coal, Cream, Dove, Espresso, Fire Engine Red, Fog, Fuchsia, Grey, Harness Brown, Hazelnut, Henna, Iolite, Iris, Ivory, Khaki, Mango, Mist Blue, Mocha, Navy, Ocean, Oxblood, Pebble, Plum, Saddle, Sandstone, Smoke Grey, Star, Stone, Tan, Taupe, White and Wine

## SPECIFICATIONS

### performance characteristics

### PERFORMANCE LEATHER

<b>EN ISO 4045</b>	
DETERMINE Ph & Ph (DIFFERENCE FIGURE)	Min 3,2
<b>ISO105/B02</b>	
	Grey Scale ≥ 3 on specimen
COLOR FASTNESS OF LEATHER TO LIGHT: XENON LAMP	Grey Scale = 3 on Reference Blue Wool #5
<b>EN ISO 15700</b>	
COLOR FASTNESS TO WATER SPOTTING	Grey Scale ≥ 3 (No permanent swelling)
<b>ISO 11641</b>	
COLOR FASTNESS OF LEATHER TO PERSPIRATION	80 Cycles ≥ 3.5
<b>EN ISO 11640</b>	
COLOR FASTNESS OF LEATHER TO RUBBING	500 Cycles Dry ≥ 4 250 Cycles Wet ≥ 3.5
<b>EN ISO 11644</b>	
FINISH ADHESION	3 N/cm
<b>EN ISO 3376</b>	
	Tensile Strength ≥ 8 Mpa
MEASURE TENSILE STRENGTH AND % ELONGATION	% Elongation ≤ 80%
<b>EN ISO 5402</b>	
FLEXING ENDURANCE (FLEXOMETER METHOD)	50,000 Cycles (no finish damage cracks)
<b>EN ISO 17233</b>	
COLD CRACK RESISTANCE OF FINISH	-15°C (no finish cracks)
<b>EN ISO 3377-1</b>	
TEAR STRENGTH (SINGLE EDGE TEAR)	>20 N Minimum

### flame resistance

CA TB 117 - 2013	Complies
NFPA - 260 CIGARETTE IGNITION	Class 1
FMVSS 302	Complies

